

Thin-client computing starts here



SIMPLE

POWERFUL

FLEXIBLE

LOW COST, HIGH PERFORMANCE, LEGACY I/O-FREE THIN CLIENT FOR A PURE SERVER-BASED COMPUTING ENVIRONMENT.

Key Features

Key Benefits

Plug-and-play connectivity, with small/zero footprint and power cord

Easier to install, connect, and use out of the box for server-based computing

Stateless device

Simple install, no batteries, no fans

Modular design connects to any VESA standard monitor

Freedom to choose the monitor that best suits your needs

Supports ICA and RDP protocol

Gives administrators the flexibility to choose the protocol that fits their needs

Multiple session support and seamless Windows

Increased productivity

2-3x faster ICA performance than most computers

Assures maximum user productivity and device life

Wi-Fi® 802.11b USB wireless option

Reduce wiring costs, easy to create temporary networks

Simple Wyse Rapport management

Manages with server-based text files or enterprise class Wyse Rapport

Supports DHCP management

Permits reconfiguration, firmware upgrades, and customized configurations — from administration server or other desktops

Three-year Buyer's Protection Plan

Assurance of reliability, availability, and performance, from the industry leader

**Secure, Managed,
Affordable, Reliable,
Thin Clients**

The Winterm™ 1200LE is a simple terminal for those who need a completely centralized desktop management option. Because the Winterm 1200LE is a completely stateless device, all of the terminal's settings are saved on the server, allowing for more control over the desktop experience. The display-based operating system provides optimized Citrix® ICA and Microsoft® RDP performance, and with all terminal management performed at the server (using simple text files), it is the most easily managed thin client.

The incredibly simple Winterm 1200LE is ideal for users in a LAN environment who use a standard suite of office productivity applications, plus email, and Internet browsing, and who utilize network-based peripherals.

The Winterm 1200LE has a tiny footprint, an attractive design, and can be mounted easily on the wall or the back of your monitor. It comes with fully integrated 16-bit stereo sound capability, 10/100Base-T network support, and optimized I/O with two USB ports. Plus, as with all Winterm thin clients, the Winterm 1200LE comes bundled with Wyse™ Rapport®, the device management tool that leverages the value of your IT infrastructure for maximum ROI.

Wyse® Winterm thin clients are an efficient way to deliver Windows®-based and web applications to users throughout your enterprise. Winterm thin clients provide security, manageability, affordability, and reliability beyond the desktop. They are easier to deploy and manage and much less expensive to buy and maintain than desktop computers.

Specifications

Modular Thin Appliance

- Integrated Citrix ICA and RDP protocols standard with 32MB on board RAM

Display Support ¹

- VESA monitor support, with DDC for automatic setting of resolution and refresh rate
- Colors: 256 (8-bit) or 65,536 (16-bit)
- Video: selectable, up to 1280x1024
- Flicker-free, 85 Hz noninterlaced refresh rate
- ELO Touchscreen with USB

Audio ^{1,2}

- Output: 1/8-inch mini, full 16-bit stereo, 48 KHz sample rate
- Input: 1/8-inch 8-bit mini microphone level

Input/Output/Peripheral Support

- Keyboard: enhanced USB with Windows keys (104 keys) included³; low profile design with two-position tilt; integrated PS/2 mouse port; detachable 5-foot (1.5-meter) cable
- Wheel mouse support for optional third party mouse
- Mouse: PS/2 mouse included
- Local and/or network printers on ICA or LPD
- VGA-type video output (DB-15)
- Two USB ports: one port dedicated for USB keyboard, one port available for peripherals (check www.wyse.co.uk for supported peripherals)
- Optional USB to serial and USB to parallel converter cable (check www.wyse.co.uk for supported peripherals)
- Optional wall mount bracket, CRT mount bracket, or bracket to securely mount to the back of LCD panels using VESA compliant mounting holes

Networking

- TCP/IP with DNS and DHCP
- 10/100Base-T Fast Ethernet, twisted pair (RJ-45)
- Point-to-Point Protocol (PPP)
- Windows 2000 RAS support
- Wi-Fi 802.11b USB option
- Multiple master browser support on ICA
- Supports Citrix load balancing on ICA
- DHCP support for automatic firmware upgrades and unit configuration
- Network printing via LDP
- PPPoE to connect to WAN via DSL
- Simple Network Time Protocol (SNTP)

Communication Protocols/ Terminal Emulations Supported

- ICA and RDP, NFuse Lite Client resident

Server OS Compatibility/Support

- Citrix WinFrame
- Citrix MetaFrame
- Microsoft Terminal Server Edition
- Microsoft Server 2000 and 2003

Set-Up and Configuration

User Interface

- Stateless architecture
- All configuration stored on server
- Keyboard language support: Belgian Dutch and French², Brazilian², Canadian French, Danish², Dutch², Finnish², French, German, Italian, Norwegian², Polish², Portuguese², Spanish, Swedish², Swiss French², Swiss German², U.K. English, U.S. English, and more

Configuration

- Configurable automatic login
- Individual scripting
- Remote management, configuration, and upgrades through Wyse Rapport software (agent and Workgroup edition included)

Physical Characteristics

- Height: 1.70 inches (4.3cm)
- Width: 7.64 inches (19.4cm)
- Depth: 6.18 inches (15.7cm)
- Shipping weight: 7.7lbs (3.5kg)

Environmental

Temperature range

- Powered on: 32° to 104°F (0° to 40°C)
- Powered off: -14° to 140°F (-10° to 60°C)
- Convection cooling, fanless design

Humidity

- 20% to 80% noncondensing
- Operating altitude range
- 0 to 10,000 feet (0 to 3,050 meters)

Power

- Worldwide auto-sensing 90-264 VAC, 47-63 Hz
- Wake-on-LAN ready

Regulatory Compliance

Ergonomics

- EK 1/59-98, EK 1/60-98

Safety

- UL 1950, CSA 950
- TÜV-GS approved
- EN 60950 approved

RF interference

- FCC Class B
- CE mark
- EN55022B
- VCCI
- C-Tick

Warranty

- Three-year Buyer's Protection Plan (one-year hardware warranty, with service extended to three years free with registration in the first 90 days)

Customer Service

- For Information, or for the nearest Wyse Customer Service Center, visit the Customer Support section of www.wyse.co.uk or send an email to support@wyse.co.uk.

WYSE

Wyse Technology (UK) Ltd
1 The Pavilions, Ruscombe Park,
Twyford, Berks RG10 9NN, England
+44 (0)118 934 2200
<http://www.wyse.co.uk>

Wyse Technology GmbH
Humboldtstr. 10
D-85609 Aschheim-Dornach, Deutschland
+49-(0)89-46 00 99-0
<http://www.wyse.de>

Wyse Technology
Immeuble Mercure, 6 Parc Club Ariane
F-78284 Guyancourt Cedex, France
+33 (0)1 39 44 00 44
<http://www.wyse.fr>

Wyse Technology Australia
Level 1, 100 Miller Street
North Sydney
New South Wales 2060, Australia
+61 2 9492 0180
<http://www.wyse.com.au>

Wyse Technology Inc.
3471 North First Street
San Jose
California 95134-1801, USA
+1 (408) 473 1200
<http://www.wyse.com>

Winterm Model 1200LE



¹Monitor or speakers and microphone not included. ²Requires support by server OS and protocol. ³Keyboard not included with international models.