

10M / 20M / 30M True 4K HDMI Active Optical Cable

VE781010 / VE781020 / VE781030


ATEN VE781010 / VE781020 / VE781030 True 4K HDMI Active Optical Cables utilize AOC technology that enables conversion between input signals and optical signals for optimum high bandwidth data transmissions. The EMI-resistant optical cables come in 10, 20, and 30 m with full support of True 4K resolutions. They're fully compliant with HDCP 2.2 standards and meet HDMI 2.0 specifications including 3D, deep color, and data rates up to 18 Gbps. Supported Dolby True HD and DTS-HD Master Audio, the optical cables guarantee lossless audio signal transmissions. The VE781010 / VE781020 / VE781030 optical cables are ideal solutions for extending the reach of your digital signage in a wide range of settings, such as traffic stations, shopping centers, and hospital facilities.



VE781010 / VE781020 / VE781030

Features

- Supports resolution up to True 4K (4096 x 2160 @ 60 Hz 4 : 4 : 4)
- HDMI (3D, Deep Color, True 4K, HDR, ARC); HDCP 2.2 compliant
- Extends True 4K signals up to 30 m
- Reduces EMI (electromagnetic interference) and RFI (radio-frequency interference) for lowered noise interference and reliable signal transmission
- High data transfer rate of 18 Gbps
- Supports multi audio channels – Dolby TrueHD and DTS-HD Master Audio
- A range of cable lengths, available in 10, 20, and 30 m
- Robust cable pulling strength (Max.10 kg) and compression load resistance (Max.50 kg)
- Plug-and-play



Specifications

	VE781010	VE781020	VE781030
Cable Length	10 m / 32.8 ft	20 m / 65.6 ft	30 m / 98.4 ft
Cable Type	Hybrid type with optical fiber (OM3) and copper wire		
Video Input	1 x HDMI 19-pin Type-A Male		
Video Output	1 x HDMI 19-pin Type-A Male		
Video	18 Gbps (6 Gbps per Channel)		
Max. Data Rate	600 MHz (Max.)		
Max. Pixel Clock	600 MHz (Max.)		
Max. Resolutions / Distance	Up to 4096 x 2160 / 3840 x 2160 @ 60 Hz (4 : 4 : 4) / 10 m *Color sub-sampling: 4 : 4 : 4 / 4 : 2 : 2 / 4 : 2 : 0 *Color Depth: 30 / 36 / 48 bit	Up to 4096 x 2160 / 3840 x 2160 @ 60 Hz (4 : 4 : 4) / 20 m *Color sub-sampling: 4 : 4 : 4 / 4 : 2 : 2 / 4 : 2 : 0 *Color Depth: 30 / 36 / 48 bit	Up to 4096 x 2160 / 3840 x 2160 @ 60 Hz (4 : 4 : 4) / 30 m *Color sub-sampling: 4 : 4 : 4 / 4 : 2 : 2 / 4 : 2 : 0 *Color Depth: 30 / 36 / 48 bit
Compliance	HDMI (3D, Deep Color, True 4K, HDR, ARC); HDCP 2.2		
Communication	TMDS / HDCP 2.2 / EDID / CEC		
Audio	PCM 8-channel, Dolby Digital True HD, DTS-HD Master Audio		
Input	PCM 8-channel, Dolby Digital True HD, DTS-HD Master Audio		
Output	PCM 8-channel, Dolby Digital True HD, DTS-HD Master Audio		
Conductor	7 x Tinned Copper wire strand 4 x OM3 Optical Fiber (50 / 125 um)		
Construction	Bend Radius: 20 mm (Min.) Compression Load Resistance: Max. 50 kg (500 N) Cable Filler: Kevlar		
Notification	Cable Marking: ATEN INTERNATIONAL --- HIGH SPEED HDMI HYBRID ACTIVE OPTICAL CABLE 4K @ 60 Hz 18 Gbps -- PVC CE EU RoHS EC ZONE / DEVICE * NO external power required		
Certifications	Safety and Emission: CE / FCC / RoHS / REACH / UL VW-1 EMC Class-A / Class-B		
Certifications	DC5.0V:0.25W:0.05A		
Power Consumption	DC5.0V:0.25W:0.05A		
Jacketed	PVC (85P); Color: Black		
Material	PVC (85P); Color: Black		
Environmental	0 °C - 50 °C		
Operating Temperature	-20 °C - 70 °C		
Storage Temperature	0 - 85 % RH, Non-Condensing		
Humidity	0 - 85 % RH, Non-Condensing		
Physical Properties	Connector Case: Zinc Alloy		
Housing	Connector Case: Zinc Alloy		
Weight	0.35 kg	0.65 kg	0.90 kg
Cable Outer Dimension	4.5 mm (± 0.2 mm)		

Product information is subject to change without prior notice.

ATEN International Co., Ltd.

3F, No.125, Sec. 2, Datung Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com

Released: 05/2022 V3.0

© Copyright 2022 ATEN® International Co. Ltd.
ATEN and the ATEN logo are registered trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.
The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

